

# ASR1101M ASR1101M-D

## Vandal-proof RFID Reader



### Technical Specification

Mode	ASR1101M	ASR1101M-D
------	----------	------------

### System

Main Processor	8 Bit
----------------	-------

### Read

Read Format	13.56MHz	125KHz
-------------	----------	--------

Read Range	1cm-3cm (max.)
------------	----------------

Reading time	<0.1s
--------------	-------

### Function

Tamper Alarm	Yes
--------------	-----

### Interface

To Controller	RS485, Wiegand34(Wiegand 26 optional)
---------------	---------------------------------------

### General

Keyboard	12Key(0-9, *, #), number key 5 is a braille button
----------	--

LED Indicator	Blue backlight
---------------	----------------

Beep Tone	Buzzer
-----------	--------

Ingress protection	IK08
--------------------	------

Power Supply	9V-15V DC/100mA
--------------	-----------------

Operating Temperature	-30°C to +60°C
-----------------------	----------------

Working Humidity	≤95%
------------------	------

Dimension(W×D×H)	110mm×85mm×26mm
------------------	-----------------

Weight	0.5kg
--------	-------

Working Environment	Indoor
---------------------	--------

### Certificates

CE	Yes
----	-----

FCC	Yes
-----	-----

### Features

- Support RS485, Wiegand34 protocol(Wiegand 26 optional)
- 13.56MHz(Mifare)
- 125KHz(EM-ID)
- All-metal buttons with blue backlight
- Red and Green indicator LEDs
- Watch dog function ensure device free from halting
- Surface mounted installation



### Dimensions

