

# DH-PFS5924-24X

## DH-PFS5924-24X (L2+ Managed Switch)



### Product Overview

DH-PFS5924-24X is a type of managed switch with layer 2+, which adopts 350G back panel design structure and realizes many functions such as route, port mirroring, port isolation, ARP binding, spanning tree, VLAN, ACL, DHCP snooping, multicast, link aggregation and etc. It is the best choice in small and medium-sized enterprises.

### Features

#### ■ Powerful Processing Capacity

Based on VCore-III MIPS-based CPU powerful, stable processing capacity;  
DH-PFS5924-24X provides exchange capacity up to 350Gbps, port full linear filter forward 35.7Mpps;  
Guarantee large flow data forward of backbone network without block.

#### ■ Perfect Security Control Strategy

Support user IP+MAC address certification based on port, 802.1X certification based on port, remote Radius、NAS certifications;  
Support IP ACL、MAC ACL、Vlan ACL、support ACL function based on the third, fourth layer, effectively defend ARP attack and virus;  
Support perfect storm control function, able to realize suppression over broadcast, multicast and unicast storm;  
Support specific ARP intrusion detection function; effectively prevent increasingly popular "ARP cheat attack" implemented by hacker or attacker via ARP message;  
Support IP Source Guard features; prevent illegal address counterfeit including MAC cheat, IP cheat, MAC/IP cheat and Dos attack brought by large flow address counterfeit.  
Provide DHCP snooping function, it can realize to snoop the MAC address, IP address and various information of access users via creating and maintaining DHCP Snooping binding table, which has solved the IP and port tracking of DHCP users.

#### ■ Perfect Reliability Protection Mechanism

It can implement flow classification and speed limit upon the packet which is sent to CPU via CPU protection strategy, which is to avoid illegal packet causing resource consumption upon CPU;  
Support several spanning tree protocols such as STP, RSTP, MSTP and etc, which can realize fast convergence and improve fault-tolerant capability;  
Support industrial ERPS spanning protocol, whose convergence time is within millisecond, which guarantees no interruption for services. Besides, the protocol is simple and reliable,

## DH-PFS5924-24X

which makes it greatly convenient for users to manage and plan network;

### ■ Convenient Management and Maintenance

It can implement simple and convenient operation upon various functions of the switch via easy visual WEB interface (support http and https protocol);

Support SNMP protocol to configure management for the device, provide convenience about centralized device management for small and medium-sized enterprises;

Support CLI configuration, manage via Telnet and Console port, which is suitable for professional network managers;

Support SSH2.0 and other encryption modes, make management much safer;

Support PDP, LLDP protocol, which make network management much simpler;

Support NTP clock protocol, which can sync network time automatically;

### Technical Specifications

Model	DH-PFS5924-24X
Interfaces	1000M SFP port x 16
	Combo 1000BASE-T/SFP port x 8
Management Ports	One Console port
Reset Button	One Restore Factory Default Button
Switching Capacity	350Gbps
Packet Forwarding Rate	35.7Mpps
Working Temperature	-10~55°C
Storage Temperature	-40~70°C
Operating Humidity	5%~95% Non-condensing
Dimensions	440(L)×285(W)×44.5(H)mm
Weight	<5Kg
Input Voltage	AC: 110~240V/50~60Hz
Power Consumption	<50W

### Service Characteristics

Model	DH-PFS5924-24X
Protocol Standard	IEEE 802.3ad, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3ae, IEEE 802.3x, IEEE 802.3az,
MAC Table	32K
VLAN	4K
	Port-based VLAN
	802.1Q Standard VLAN
	MAC-based VLAN
	Protocol-based VLAN

## DH-PFS5924-24X

Spanning Tree	STP
	RSTP
	MSTP
Loop Protection	ERPS
Loopback Detection	Support
port Aggregation	Up to 14 aggregation groups, and up to 8 GE ports for each group;
	LACP; Manual aggregation
Mirroring	Support many-to-one port mirroring, no limit for the quantity of mirroring source port;
Flow Control	Support half-duplex based on back pressure type control;
	Support full duplex based on PAUSE frame;
Port Speed Limit	Support
IP Routing	Static Routing
Multicast	IGMP Snooping
	MVR (Multicast VLAN Registration)
DHCP	DHCP Client;
	DHCP Server;
	DHCP Snooping;
Storm Suppression	Support suppression upon broadcast, multicast, unicast
Security Features	Hardware supports IP ACL, MAC ACL, VLAN ACL;
	Hardware supports IP+MAC binding based on port;
	Support IP Source Guard
	Support ARP Detection
	Support IEEE802.1x port authentication
	Support Radius authentication
	Support the user classification management, and password protection
System Maintenance	Support the configuration file upload/download
	Support the updated packet upload
	Restore default configuration via WEB
	Support system logs
	PING
Network Management	WEB(http and https protocol)
	CLI
	Telnet
	SSH 2.0
	SNMP
	RMON
	LLDP
	Support the NTP client

# DH-PFS5924-24X

---

## Accessories

Model	
PFT3950	1.25G 850nm,500m,LC, Multi-mode
PFT3960	1.25G 1310/1550nm,20km,LC, Single-mode
PFT3970	1.25G 1550/1310nm,20km,LC, Single-mode

---

### Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email:overseas@dahuatech.com

www.dahuatech.com

\*Design and specifications are subject to change without notice.

© 2012 Dahua Technology Co., Ltd.